

Kerry Abrasives' new Hot Pressed Rubber Bonded Grinding Wheel opens up a whole new dimension for precision flute grinding applications!

Advantages of Hot Pressed Rubber Bonded Wheels:

- Outstanding high quality surface finish
- Dense bond structure, therefore:
- Excellent profile holding capabilities
- Absolutely no burn
- Long life wheel
- Ability to run at high peripheral speeds
- Better stability and more economic than industry standard resin bonded wheels.

Main Applications:

- Flute grinding with CNC grinding machines
- Grinding teeth in circular saw blanks (in package clamping)
- ...and many more specialist applications.

**Kerry Abrasives are committed to delivering Quality and Expertise – Here is what you can expect:**

- **Improved Grind:** Smooth surface finish without burn, high stock removal rate and stable profile.
- **Better Productivity:** Reliable, consistent quality and access to technical knowledge.
- **Technical Support:** In-house technical dept. available to offer support with all issues.
- **Material Range:** Superbly suited to grind HSS tool steel; and equally suited for other hard metals.
- **Commitment:** Expert advice on correct wheel specification for your application and trial wheels for testing.

### Typical Specifications

- Wheel sizes: 150 to 250mm with thickness from 2mm to 15mm.  
Grit sizes: Aluminium Oxide (A) 36 to 400grit and Black (BC) or Green (GC) Silicon Carbide also available on request.  
Customised solutions: Other wheel sizes and specifications are available to suit your needs.

